

# Kwikset



## SMARTCODE 260™

KEYPAD ELECTRONIC LOCK

**MICROBAN**  
ANTIMICROBIAL TECHNOLOGY

**SMARTKEY**  
SECURITY™

The SmartCode™ 260 Keypad Electronic Deadbolt offers a sleek 10-button design, Microban® Antimicrobial Technology protection and the convenience of one-touch locking. This keyless deadbolt comes in a traditional or contemporary design, which perfectly complements the Kwikset Prescott and San Clemente handlesets.

### Features

- The responsive keypad provides bright LED illumination for easy code access
- Fast motorized deadbolt with one-touch locking
- Auto-locking after 30 seconds or select custom auto-lock time delay
- Protected with Microban® Antimicrobial Technology built into the keypad and finish

### User Codes

- Up to 50 user codes for family, guests and service professionals
- Programming code for improved access code management



#1 SELLING U.S. LOCK BRAND\*

\*Source: TraQline US quarterly brand unit share report, Q4 2006 through Q2 2022

## Specifications

|                          |                                                                                                          |
|--------------------------|----------------------------------------------------------------------------------------------------------|
| <b>Battery</b>           | Uses 4 x AA 6V alkaline cell batteries with approximately 1 year battery life                            |
| <b>Function</b>          | Single cylinder deadbolt                                                                                 |
| <b>Door Prep</b>         | 1 1/2" (38mm) or 2 1/8" (54mm) diameter cross bore hole and 1" diameter edge bore hole                   |
| <b>Backset</b>           | Adjustable 2 3/8" (60mm) or 2 3/4" (70mm)                                                                |
| <b>Door Thickness</b>    | 1 3/8" (35mm) to 1 3/4" (44mm) standard. Thick door service part available for 2-1/4" (57mm) thick doors |
| <b>Faceplates</b>        | 1" (25 mm) x 2 1/4" (57 mm) round corner faceplate with drive-in collar standard                         |
| <b>Strikes</b>           | 2 3/4" (70mm) x 1 1/8" (29mm) round corner 4 hole strike                                                 |
| <b>Bolt</b>              | 1" (25mm) throw, steel bolt with anti-saw security pin                                                   |
| <b>Door Handing</b>      | Reversible                                                                                               |
| <b>Cylinder</b>          | SmartKey Security™ with 2 KW1 keys                                                                       |
| <b>Temperature Range</b> | Exterior: -40°F to 150°F (-40°C to 66°C)<br>Interior: 32°F to 130°F (0°C to 54°C)                        |
| <b>Humidity</b>          | Exterior: 100% condensing<br>Interior: 30% to 95% non-condensing                                         |
| <b>Codes</b>             | Up to 50 user codes and 10 one-time user codes with optional programming code                            |

## Dimensions

Exterior

Diagram showing the exterior and side views of the Traditional lock. The exterior view shows a rectangular lock with a keypad and a circular handle. Dimensions A, B, and C are indicated: A is the width, B is the height, and C is the depth.

Interior

Diagram showing the interior and side views of the Traditional lock. The interior view shows a rectangular lock with a circular handle. Dimensions A, B, C, and D are indicated: A is the width, B is the height, C is the depth, and D is the thickness of the handle.

**Traditional**

| Design   | A                                            | B                                           | C                                          | D                                            |
|----------|----------------------------------------------|---------------------------------------------|--------------------------------------------|----------------------------------------------|
| Exterior | 2 <sup>13</sup> / <sub>16</sub> "<br>(71 mm) | 5"<br>(127 mm)                              | 1"<br>(25 mm)                              | ---                                          |
| Interior | 2 <sup>3</sup> / <sub>4</sub> "<br>(70 mm)   | 5 <sup>1</sup> / <sub>2</sub> "<br>(140 mm) | 1 <sup>1</sup> / <sub>8</sub> "<br>(29 mm) | 1 <sup>11</sup> / <sub>16</sub> "<br>(43 mm) |

Exterior

A line drawing of the exterior of a Contemporary lock. It features a rectangular faceplate with a keypad at the top and a circular handle at the bottom. Dimension A indicates the width of the faceplate, and dimension B indicates the height.

A line drawing showing the side profile of the Contemporary lock. Dimension C indicates the depth of the lock body.

Interior

A line drawing of the interior of the Contemporary lock. It shows a rectangular faceplate with a circular handle. Dimension A indicates the width of the faceplate, and dimension B indicates the height.

A line drawing showing the side profile of the Contemporary lock. Dimension C indicates the depth of the lock body, and dimension D indicates the height of the handle assembly.

### Contemporary

| Design   | A                                          | B                                            | C                                          | D                                            |
|----------|--------------------------------------------|----------------------------------------------|--------------------------------------------|----------------------------------------------|
| Exterior | 2 <sup>3</sup> / <sub>4</sub> "<br>(70 mm) | 4 <sup>9</sup> / <sub>16</sub> "<br>(116 mm) | 1"<br>(25 mm)                              | ---                                          |
| Interior | 2 <sup>3</sup> / <sub>4</sub> "<br>(70 mm) | 5 <sup>1</sup> / <sub>2</sub> "<br>(140 mm)  | 1 <sup>1</sup> / <sub>8</sub> "<br>(29 mm) | 1 <sup>11</sup> / <sub>16</sub> "<br>(43 mm) |

## Easy Installation

- Replaces existing door hardware with just a Phillips screwdriver
- No hard wiring needed and fits all standard doors
- Download the free **BILT** app featuring 3D instructions for quick and easy installation

## Innovative Security

- BHMA Grade 2 certified
- 20 Minute fire rating - UL certified
- Featuring SmartKey Security™

## Finishes



**992600-001**  
Polished Brass **LO3**  
260 TRL L03



**992600-002**  
Satin Nickel **15**  
260 TRL 15



**992600-003**  
Venetian Bronze **11P**  
260 TRL 11P



**992600-004**  
Satin Nickel **15**  
260 CNT 15



**992600-005**  
Polished Chrome **26**  
260 CNT 26



**992600-006**  
Matte Black **514**  
260 CNT 514

FINISH AND  
**LIFETIME WARRANTY\***  
MECHANICAL  
  
ONE YEAR  
ELECTRONIC WARRANTY\*

\*See [kwikset.com/support/warranty](http://kwikset.com/support/warranty) for the lifetime limited mechanical and finish warranties and one-year limited electronics warranty.

\*Consulte [kwikset.com/support/warranty](http://kwikset.com/support/warranty) para ver las garantías mecánicas y de acabado limitadas de por vida y la garantía limitada de un año de los electrónicos.

**Kwikset**

19701 DaVinci, Lake Forest, CA 92610 • [Kwikset.com](http://Kwikset.com) • 1-800-327-LOCK

© 2022 Spectrum Brands, Inc. Kwikset is a trademark of Spectrum Brands, Inc. Lake Forest, CA 92610 • KW-1167526